


Technical Data Sheet

ALIS Teak Oil No. 567

N means **LIVOS neutral** for the allergy-prone and chemically sensitive

Without orange oil

Application range	For interior and exterior use on teak wood.
Technical qualities	Free of cobalt. Removes light soiling, refreshes and highlights the structure of the wood grain. After complete drying water-repellent and does not form a layer. Without UV protection.
Full declaration	Isoaliphates, linseed oil, linseed oil - stand oil - natural resin ester, and drying agents free of lead (Mn, Zr).
Colors	Clear to slightly honey-colored (Gardner color index: approximately no.5)
Application method	Put some Teak Oil on a cloth and rub on sparingly, i.e. very thinly, in the direction of the wood grain. Polish after 30-60 minutes. Surface should not be sticky anymore, otherwise apply again a few drops and polish until it is no longer sticky. For heavier soiling give 10 – 20 minutes to react, remove with dirt and then apply sparingly. Always do a test application on an inconspicuous area to ensure compatibility e.g. with previously used oils.
Coverage	First coat: 1 liter (1.06 quart) is sufficient for approximately 30 m ² (323 ft ²), i.e. 30ml/m ² . Second coat: 1 liter (1.06 quart) is sufficient for approximately 84 m ² (904 ft ²), i.e. 12ml/m ² . Could be considerably less or more, depending on the condition and the absorbency of the surface. Test application!
Drying time	At 23 °C (73 °F) and 50% relative humidity: approximately 8 - 16 hours under good light- and ventilation conditions.
Specific gravity	Approximately 0.84 g/ml.
Safety advice	Refreshment with ALIS Teak Oil once the wood is dry. Plant oil based products often lead to drying delays due to a lack of oxygen and light. This can result in long lasting oil smell. Apply only one sparing coat and leave the cabinet door open for one week. If the stain drips off or bubbles appear during application, an incompatibility exists through the pre-treatment or it has been sanded to smooth. Coarser sanding may possibly create remedy. Always be sure to store and then dispose of cleaning cloths, polishing pads, sponges, etc. that are still wet or even slightly moist with ALIS Teak Oil No. 567 in an airtight metal container or in water, as there is a danger of spontaneous combustion caused by the plant oil content. The liquid or applied product is not self-ignitable. H304 May be fatal if swallowed and enters airways. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P501 Dispose of waste according to applicable legislation. P405 Store locked up.
 Danger	
Disposal	According to locally regulated laws.
Container sizes	0.25 l; 0.75 l; 2.5 l.
Storage	Cool and dry. Shelf life: unopened at least 4 years.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at www.livos.de. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.

August 2017